

Image

BOATS LTD



Image 10.5m Prestige

Standard Specifications

- 10.5m Hardtop [LOA] 10.75m
- 6mm hull, 5mm sides, 4mm top sides and roof 2.95 beam
- 19 Deg deadrise
- 2 bilge pumps 2000 gph 12v fitted plus 1 float switch
- 4 Rod Holders
- Anchor light
- Boarding ladder x 2
- Boarding platforms
- Bow rail - heavy duty
- Compass
- Deck light
- Double bed insert
- Zipwake Electric trim tabs and gauges
- Fit zinc block on transom
- Front hatch
- Front squabs
- Handrail on cabin
- Lined cabin and wheelhouse - vinyl
- Navigational lights fitted
- Side storage, shelves, pockets on deck
- Sliding side windows
- Strip lighting for under cup holder
- Strip lighting for under bulwarks
- Extended duckboard with cage
- Binnacle door with storage
- Extra bollard up front
- 1150 litre fuel tank
- Shower cubicle with toilet Calfont and rose fitted 7 Litre
- VHF fitted

Extras

- Stress free winch, 150m Rope & Chain Mighty 1700W
- Rocna SS 15KG
- Rocna Anchor 15KG
- Maxwell free fall 560
- Bunk beds
- Cup holder
- Deck pump and hose
- Frigonautica 90L MFC/2
- Gas bottle alloy
- Gas shut off valve and BEP sensor
- Heater - 4 kw diesel with vents on dash
- Heated ducting into toilet
- Diesel tank
- Kitchen joinery
- Ladder on side of wheelhouse
- Lockup wheel house with drop down windows
- Complete paint work for 50/50
- Radio Fusion MS-UD750 player with AM/FM aerials fitted
- Rocket launcher on roof with 8 rod holders
- Rubber on roof (6 sheets)
- Sink in shower with hatch
- Speakers fitted outside cabin
- Speakers fitted inside cabin x 4
- Spotlight - fitted into rail
- Storage hatch - inside - hinged
- Storage hatch - outside
- Table
- Trailer hydraulic sensor brakes with s/s hubs & calliper
- Surf grip on bulwarks and front of cabin full sheets
- Teak deck flooring
- Walk through transom - sliders
- Water pump, fitted, fresh water
- Window washers
- Windows rounded
- Pot hauler with pulley
- Stove 4 burner oven SA3002 fitted
- Black water tank
- Bow thruster
- Frigonautica 75L Drawer Freezer
- Extra electrical sockets - each for electric reels
- Insulation walls, bunks and ceiling
- Extra rub rail along exterior of hull
- 2 drawers into front of flip flop



- Keel strip
- Rod rack fitted in shower
- GARMIN
- Garmin GMR Fantom 24" dome
- Garmin 8417 head unit
- GSD 26 CHIRP professional sonar module
- GSD 25 Garmin
- GPS 19 x NMEA 2000
- NMEA 2000 starter kit
- SS 175 TH Transducer
- 1 KW GT51 TH Transducer
- VPC023R NZ map
- GPS map 752 drift alarm
- Cables
- Garmin Heading Sensor
- VHF210i AIS
- Fitting of VHF
- VHF Aerial and AM/FM Aerial and bases and fitting
- SWB Core Pack
- Fitting of Garmin units
- Radar to sit on a bracket - height to be disc
- Inter connection cable
- Reactor 40CCU
- Fitting of radar
- Optimus Sea Station
- Additional settlement discount 5% on sea station
- Fitting of Optimus Sea Station
- Additional Joystick
- Solar panels & BEP Regulator
- Sink in bait board
- Tap out back
- Bow Thruster
- Underwater lights Bluefin
- Live bait tank with glass and pump

- Hella Lights
- Fresh water tank sender
- Black water tank sender
- Custom hatches from USA
- Sight Gauge on tank
- 2 x S/S Cleats
- Stainless Steel Rod Holders (Bluewater series Rotating and fitting)
- Handrails under boarding platform
- 1524mm 8518 High gloss over laminate with sealer
- Powder coating of ladders matte black
- Accy, Extension Cable, 12-pin, 3M, VHF210/210i
- Fully welded trunkets under roof
- Dive bottle holder (powder coated)
- Transom tow points x 4
- Extra shelves on island bait station doors
- Recessed dish for cabin ceiling light
- Bilge plate with holes drilled
- Trunkets inside port starboard, transom walk through internal shelves
- Suzuki DF325ATX
- Helm Seat

MODEL	DF325A
RECOMMENDED TRANSOM HEIGHT mm (in.)	X : 635 (25) XX : 762 (30)
STARTING SYSTEM	Electric
WEIGHT kg (lbs.) *1	X : 330 XX : 339
ENGINE TYPE	V6 - 55" DOHC 24-Valve
Valve Train Drive	Chain with Variable Valve Timing
FUEL DELIVERY SYSTEM	Electronic Fuel Injection
NO. OF CYLINDERS	6
PISTON DISPLACEMENT cc (cu.in.)	4,390 (267.9)
BORE x STROKE mm (in.)	98 (3.74) x 97 (3.82)
MAXIMUM OUTPUT kW (PS)	239.0 (325)
STEERING	Remote
FULL THROTTLE OPERATING RANGE rpm	5,300 - 6,300
OIL PAN CAPACITY l (U.S./Imp. qt.)	8.0
IGNITION SYSTEM	Fully-transistorised
ALTERNATOR	12V 54A
ENGINE MOUNTING	Shear Mount
TRIM METHOD	Power Trim and Tilt
GEAR RATIO	2.29:1
GEAR SHIFT	F-N-R (Drive-by-Wire)
EXHAUST	Through Prop Hub Exhaust
PROPELLER SELECTION (Pitch) *2	FRONT: 3x15 1/2x15.0-31.5 REAR: 3x15 1/2x15.0-31.5



Proudly Powered By

